





**“EXACT FIT”
Replacement
Filter Element
Specification**



PNEUMAFIL PART NUMBER	A43410C1	A43411C1
DONALDSON PART NUMBER	P19-1236	P19-1238
Shape	Cylindrical	Conical
Effective Filtration Area	226 F² / 21 m²	275 F² / 25.5 m²
Length of Element without Gasket	26" / 660 mm	26" / 660 mm
Outer Diameter	12.75" / 324 mm	17.5" x 12.75" / 445 mm x 324 mm
Inner Diameter	8.38" / 213 mm	13" x 8.38" / 330 mm x 213 mm
Number of Pleats	330	402
Pleat Depth	1.9" / 50 mm	1.9" / 50 mm
Media	Cellulose/ Polyester Blend	
Inner & Outer Liners	G60 Galvanized Expanded Steel	
Endcaps	G60 Galvanized Steel with Media Potted in 2-Part Polyurethane	
Gasket	Molded Polyisoprene	
Test Data	per LMS Technologies, Inc. Report No. 211	
Test Airflow Rate	1533 cfm	
Initial Resistance	0.713" w.g. / 18.1 mm w.g.	
Initial Fractional Efficiency	Efficiency at 2.02" / 51.3 mm w.g. pressure drop	
<u>Particle Size</u> <u>Efficiency</u>	<u>Particle Size</u>	<u>Efficiency</u>
½ micron 29.5%	½ micron	100%
1 micron 53.1%	1 micron	100%
1 ½ microns 58.7%	1 ½ microns	100%
2 microns 65.3%	2 microns	100%
2 ½ microns 78.7%	2 ½ microns	100%
Average Dust Spot Efficiency	99.9%	