





**“EXACT FIT”
Replacement
Filter Element
Specification**



PNEUMAFIL PART NUMBER	A43422C1	A43423C1
DONALDSON PART NUMBER	P19-1037	P19-1039
Shape	Cylindrical	Conical
Effective Filtration Area.....	226 F ² / 21 m ²	275 F ² / 25.5 m ²
Length of Element without Gasket.....	26" / 660 mm	26" / 660 mm
Outer Diameter	12.75" / 324 mm	17.5" x 12.75" / 445 mm x 324 mm
Inner Diameter	8.38" / 213 mm	13" x 8.38" / 330 mm x 213 mm
Number of Pleats	330	402
Pleat Depth	1.9" / 50 mm	1.9" / 50 mm
Media	100% Cellulose Fiber	
Inner & Outer Liners	G60 Galvanized Expanded Steel	
Endcaps	G60 Galvanized Steel with Media Potted in 2-Part Polyurethane	
Gasket	Molded Polyisoprene	
Test Airflow Rate	1533. cfm for the pair	
Initial Resistance.....	0.75" w.g. / 19.0 mm w.g.	
Initial Fractional Efficiency Per ASHRAE Test 52.2	Efficiency at 1.73" / 43.9 mm w.g. pressure drop Per ASHRAE Test 52.2	
<u>Particle Size</u> <u>Efficiency</u>	<u>Particle Size</u>	<u>Efficiency</u>
½ micron 21.8%	½ micron	99.7%
1 micron 45.9%	1 micron	100.0%
1 ½ microns 54.1%	1 ½ microns	100.0%
2 microns 62.1%	2 microns	100.0%
2 ½ microns 74.0%	2 ½ microns	100.0%
Average Dust Spot Efficiency Per ASHRAE Test 52.1	98.1% / EU9	